

American Wire and Cable

Phone 440 235-1140 Fax 440 235-3330

TYPE	AWG	STND	MIL	TEMP	Voltage	Nominal OD
Type GPT Automotive Primary Wire - 85 C PVC						
GPT	8	19/st	.037	85	60	0.222
GPT	10	19/st	.031	85	60	0.184
GPT	12	19/st	.026	85	60	0.144
GPT	14	19/st	.023	85	60	0.118
GPT	16	19/st	.023	85	60	0.105
GPT	18	16/st	.023	85	60	0.092
GPT	20	7/st	.023	85	60	0.085
GPT	22	7/st	.023	85	60	0.078
Type HDT Automotive Primary Wire - 85 C PVC						
HDT	6	133/st	.060	85	600	0.305
HDT	8	19/st	.055	85	600	0.258
HDT	10	19/st	.046	85	600	0.212
HDT	12	19/st	.046	85	600	0.183
HDT	14	19/st	.041	85	600	0.154
HDT	16	19/st	.040	85	600	0.138
HDT	18	16/st	.037	85	600	0.123
HDT	20	7/st	.036	85	600	0.113
Type TXL Automotive Primary Wire - 125 C XLPE						
TXL	8	19/st	0.022	125	50	0.192
TXL	10	19/st	0.020	125	50	0.160
TXL	12	19/st	0.018	125	50	0.130
TXL	14	19/st	0.016	125	50	0.104
TXL	16	19/st	0.016	125	50	0.091
TXL	18	16/st	0.016	125	50	0.078
TXL	20	7/st	0.016	125	50	0.070
TXL	22	7/st	0.016	125	50	0.065
Type GXL Automotive Primary Wire - 125 C XLPE						
GXL	8	19/st	0.037	125	50	0.222
GXL	10	19/st	0.031	125	50	0.184
GXL	12	19/st	0.026	125	50	0.144
GXL	14	19/st	0.023	125	50	0.118
GXL	16	19/st	0.023	125	50	0.105
GXL	18	16/st	0.023	125	50	0.092
GXL	20	7/st	0.023	125	50	0.086
GXL	22	7/st	0.023	125	50	0.076
Type SXL Automotive Primary Wire - 125 C XLPE						
SXL	8	19/st	0.043	125	50	0.234
SXL	10	19/st	0.041	125	50	0.202
SXL	12	19/st	0.037	125	50	0.166
SXL	14	19/st	0.035	125	50	0.142
SXL	16	19/st	0.032	125	50	0.123
SXL	18	16/st	0.030	125	50	0.106
SXL	20	7/st	0.029	125	50	0.098
Put-ups: Drums (20", 30", or 42"), Reels, or Plastic Spools						

12/20/2012